

ROHS Compliant

REV A	DESCRIPTION Initial Release	DATE 06.09.08
----------	--------------------------------	------------------



Specification:

1. Current rating: 1.5 A Max.
2. Voltage Rating: 30V AC (RMS)
3. Dielectric withstanding voltage: 500 V(ac) for 1 minute.
4. Contact resistance: 30 mΩ Max.
5. Insulation resistance: 1000 MΩ Min at DC 500V.
6. Temperature range: -55°C~+105°C

PART NO.
USBA13-4M $\frac{* * *}{1 \ 2 \ 3}$

1. Insulator Color:
W: White
K : Black
2. Contact Plating:
01: Flash Gold
30: 30u" Gold
3. Shell Plating:
J: Nickel

4	Back-shell	1	Cold Rolled Steel	T=0.35mm	Cu: 40u"min. 80u"min Nickel Plated
3	Front-shell	1	Cold Rolled Steel	T=0.35mm	Cu: 40u"min. 80u"min Nickel Plated
2	Contact	4	Brass	T=0.20mm	Contact area: 0.8u"min Gold Plated over 40u"Nickel min. Solder area: 80u"min Tin Plated over 40u"Nickel min.
1	Housing	1	P.B.T	UL 94-V0	Black/White
No.	Name	Q'ty	Material	Remarks & Thickness	Finish

 PANSTRONG COMPANY LTD.				DRAWN BY		TOMMY	
				CHECKED		TOMMY	
TITLE:				USB A TYPE PLUG Wire Solder for Molding			
PART NO:				USBA4M13-4MX**			
SCALE		1:1	REV	A	UNIT	mm	

TOLERANCE UNSPECIFIED	
.x	±0.30
.xx	±0.20
.xxx	±0.10
ANG.	±1°

